

Stanley Access Technologies Series 500 Revolving Door

The Stanley Access Technologies Series 500 revolving door is an innovative manual revolving door designed for use in a wide variety of applications. It is environmentally friendly, helping to improve energy efficiency in buildings and interior comfort while reducing infiltration of dust and dirt into the building entrance.

For use in applications such as office buildings, restaurants, and banks, our surface mount revolving door is designed with the long lasting quality the industry has come to know of Stanley products. The over-head mechanical speed control will provide many years of trouble free service.

Features

- 4-Wing design
- Standard diameters 6'6", 7.0'
- Canopy heights standard 3" profile
- Standard finishes - clear or bronze anodized
- Standard anodized aluminum push bars - one per wing
- Long lasting stainless steel floor ring (see photo bottom right)
- Upper concealed collapsing mechanism
- Bookfold wing position factory set for emergency egress
- Curved laminate glass wall enclosure
- Locks - standard deadbolt
- Slim line door and enclosure sections
- Overhead speed control
- Easily removed door wings to provide fast and efficient service
- Conforms to all North American Building Codes
- One year warranty



**Stanley Access Technologies
Series 500 Revolving Door**




**Close-Up of
Collapsing Mechanism**

Stanley Access Technologies

65 Scott Swamp Road
Farmington, CT 06032
www.stanleyaccess.com

Stanley Access Technologies Series 500 Revolving Door

Four-Wing Model




Options

- Tinted glass
- Wing glass
- Quarter segment floor grille
- Roof sheets
- Canopy lighting
- Special heights
- Special finish
- Extended warranties available
- Maintenance and service contracts available

Work by others

- Installation of wall and wing glass and glazing
- Floor level
- Electrical (for lighting)

Elevation



Standard 4 Wing Door Dimensions

DOOR DIAMETER - A	OPENING WIDTH - B	ENCLOSURE DEPTH - C
*6'-6" (1981)	4'-5 1/4" (1353)	4'-10 5/8" (1489)
*7'-0" (2134)	4'-9 1/2" (1461)	5'-2 7/8" (1597)

* Denotes standard size doors in 7'-0" (2134) height. All other heights are custom fabricated and finished to suit specific job requirements. Consult factory for availability.